

LaMotte 2020 Turbidity Meters

DISTRIBUTED BY INW



APPLICATIONS

Environmental monitoring

Water/Wastewater monitoring

Construction monitoring

Stormwater runoff

LaMotte 2020 Turbidity Meters offer long-term stability, minimizing stray light and color interference

Features

- Advanced microprocessor
- Patent pending optical chamber resulting in higher accuracy and wider range
- Automatic range selection
- Range: 0-4000 NTU
- Accuracy: $\pm 2\%$
- Powered by 9V battery or optional AC power
- Records 4000 data points
- Response time: <5 seconds
- Adjustable signal averaging
- Adjustable auto shutoff
- 2020e complies with USEPA 180.1 standard with Tungsten light source
- 2020i complies with ISO 7027 standard with 860nm LED light source
- Kit comes with 0, 1, and 10 NTU standards, sample bottle, 4 sample tubes, and extra battery

INW carries a full line of LaMotte meters. Please call or email for further information. Our sales and support staff are always happy to work with you to make your project a success.

©2011 Instrumentation Northwest, Inc. All rights reserved. INW is a registered trademark of Instrumentation Northwest. Information in this document is subject to change without notice.
Doc# 9Q0095r2 10/11



SALES & SERVICE LOCATIONS

8902 122nd Avenue NE
Kirkland, WA 98033 USA
425-822-4434

FAX 425-822-8384 / info@inwusa.com

4620 Northgate Boulevard, Suite 170
Sacramento, CA 95834 USA
916-922-2900

FAX 916-648-7766 / inwsw@inwusa.com

True data, measure by measure

1-800-PRO-WELL
WWW.INWUSA.COM